

Version History

- 1.00 Original version.
 1.01 Added: "serverSoftware" parameter.

1. Request

Required variables are in **bold**.

Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Allowed Values
loginName	string	64 chars	Account Username (case sensitive)
loginPassword	string	128 chars	Account Password (case sensitive)
<i>saspSessionID</i>	string	16 chars	SASP Session ID. If this parameter is specified, "loginName" and "loginPassword" should not be specified.
orderNumber	integer		The Order Number of a Wildcard SSL Certificate ordered previously using !AutoApplySSL.
quantity	integer		The number of Additional Server Licences required.
<i>serverSoftware</i>	integer		See the !AutoApplySSL documentation for details. If omitted, the "serverSoftware" value supplied to the original !AutoApplySSL order will be used.

2. Response

2.1 MIME Type and first line

Line	Possible Value(s)
<i>Mime-Type</i>	text/plain
Line 1: <i>Status Code</i>	0 = Successful -1 = Request was not made over https! -2 = Unrecognised argument! -3 = The 'xxxx' argument is missing! -4 = The value of the 'xxx' argument is invalid! -14 = An unknown error occurred! -15 = Not enough credit! -16 = Permission denied <reason> -17 = Request used GET rather than POST!

2.2.1 If Status Code < 0

Line	Possible Value(s)
Line 2: <i>Error Message</i>	See <i>Status Code</i> Possible Value(s)

2.2.2 If Status Code = 0

Line	Possible Value(s)
Line 2: <i>Order Number</i>	Integer
Line 3: <i>Amount Debited</i>	Amount debited (in the Account's default currency)