

## Version History

- 1.0 Original version.
- 1.01 Changed: "accountStatus" is a string, not an integer.  
Changed: Descriptions of "verificationLevel" and "accountStatus".
- 1.02 Added: "loginName", "loginPassword" and "accountID" parameters.  
Added: "capLiveCCCs", "peakLiveCCCs", "currentLiveCCCs" and "authorizedDomains" response parameters.
- 1.03 Added: "resellerStatus", "webHostResellerStatus" and "epkiStatus" response parameters.

## 1. Request

The request should be POSTed (rather than GETed) to the above URL.

Required variables are in **bold**.

Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Description
Either:			
<b>saspSessionID</b>	string	16 chars	The ID of a SASP "login session"
Or:			
<b>loginName</b>	string	64 chars	Tier 1 or Tier 2 Username
<b>loginPassword</b>	string	128 chars	Tier 1 or Tier 2 Password
<i>accountID</i>	integer		Tier 2 Account ID (this parameter is required when the "loginName" and "loginPassword" are those of the Tier 1; otherwise, this parameter should be omitted)

## 2. Response

The MIME type will be `application/x-www-form-urlencoded`, because the format of the response will be the same "URL-encoded" format as the request (e.g. `name1=value1&name2=value2`).

Here are the names of the various variables that will or may appear in the response:

Variable Name (case insensitive)	Type	Description
<b>errorCode</b>	integer	Error code (see list below for possible values)
<i>errorMessage</i>	string	Explanation of error
<i>accountID</i>	integer	The SASP ID of the Account
<i>userID</i>	integer	The SASP ID of the logged-in User
<i>verificationLevel</i>	string	The level of validation performed on the company controlling the account (e.g. "Class 3")
<i>accountStatus</i>	string	The status of the account (e.g. "Not yet active", "Active", "Suspended", etc)
<i>resellerStatus</i>	string	The status of the Reseller functionality of the account (e.g. "Awaiting Authorization", "Authorized", "Rejected")
<i>webHostResellerStatus</i>	string	The status of the Web Host Reseller functionality of the account (e.g. "Awaiting Authorization", "Authorized", "Rejected")
<i>epkiStatus</i>	string	The status of the E-PKI functionality of the account (e.g. "Awaiting Authorization", "Authorized", "Rejected")
<i>capLiveCCCs</i>	integer	(Certain Tier 2 Resellers only) The maximum number of concurrently "live" CCCs that this Tier 2 is permitted to have
<i>peakLiveCCCs</i>	integer	(Certain Tier 2 Resellers only) The highest number of concurrently "live" CCCs that this Tier 2 has ever had
<i>currentLiveCCCs</i>	integer	(Certain Tier 2 Resellers only) The number of "live" CCCs that this Tier 2 currently has
<i>authorizedDomains</i>	string	A comma-separated list of domain names that have been authorized to be used in email address fields in CCCs order by this Partner. The special value "authorizedDomains=NONE" means that no domain names are authorized. (If this parameter is omitted, all domain names are authorized).

Here are the possible values for "errorCode" and "errorMessage":

errorCode	errorMessage
0	Successful
-1	Request was not made over HTTPS!
-2	'xxx' is an unrecognized argument!
-3	The 'xxx' argument is missing!
-4	The value of the 'xxx' argument is invalid!
-14	An unknown error occurred!
-16	Permission denied!
-17	Request used GET rather than POST!