

Version History

1.0 Original version.

1. Request

The request should be POSTed (rather than GETed) to the above URL.

Required variables are in **bold**.

Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Description
loginName	string	64 chars	Tier 1 Username
loginPassword	string	128 chars	Tier 1 Password
<i>organizationName</i>	string	64 chars	Tier 2 Organization Name (the % character may be used as a multi-character wildcard) If omitted, the default value is "organizationName=%", meaning that details of all Tier 2s will be returned

2. Response

The MIME type will be `application/x-www-form-urlencoded`, because the format of the response will be the same "URL-encoded" format as the request (e.g. `name1=value1&name2=value2`).

Here are the names of the various variables that will or may appear in the response:

Variable Name (case insensitive)	Type	Description
errorCode	integer	Error code (see list below for possible values)
<i>errorMessage</i>	string	Explanation of error
<i><accountID></i>	string	Each <i><accountID></i> pseudo parameter name is replaced by an actual integer Account ID. The string value is a Tier 2 Organization Name. There will be one such pseudo parameters for each matching Tier 2 account. e.g. 12345=My+Tier+2&23456=Another+Tier+2

Here are the possible values for "errorCode" and "errorMessage":

errorCode	errorMessage
0	Successful
-1	Request was not made over HTTPS!
-2	'xxx' is an unrecognized argument!
-3	The 'xxx' argument is missing!
-4	The value of the 'xxx' argument is invalid!
-14	An unknown error occurred!
-16	Permission denied!
-17	Request used GET rather than POST!