

Version History

1.0 Original version.

1. Request

The request should be POSTed (rather than GETed) to the above URL.

Required variables are in **bold**.

Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Description
loginName	string	64 chars	Tier 2 Username (case sensitive)
loginPassword	string	128 chars	Tier 2 Password (case sensitive)

2. Response

The MIME type will be `application/x-www-form-urlencoded`, because the format of the response will be the same “URL-encoded” format as the request (e.g. `name1=value1&name2=value2`).

Here are the names of the various variables that will or may appear in the response:

Variable Name (case insensitive)	Type	Description
errorCode	integer	Error code (see list below for possible values)
<i>errorMessage</i>	string	Explanation of error
<i>accountID</i>	integer	The ID of the Account on SASP that is now logged into
<i>userID</i>	integer	The ID of the User on SASP who has just logged in
<i>saspSessionID</i>	string	The ID of a new SASP “login session”

Here are the possible values for “errorCode” and “errorMessage”:

errorCode	errorMessage
0	Successful
-1	Request was not made over HTTPS!
-2	' <i>xxxx</i> ' is an unrecognized argument!
-3	The ' <i>xxxx</i> ' argument is missing!
-4	The value of the ' <i>xxxx</i> ' argument is invalid!
-14	An unknown error occurred!
-16	Permission denied!
-17	Request used GET rather than POST!