

<https://secure.trust-provider.com/products/!ResendInvitationEmailPAC>

Version History

- 1.00 Original version.
- 1.01 Added: *templateID* parameter.

Resending of the invite email for the PAC order.

1. Request

Required variables are in **bold**.
Optional variables are in *italics*.

Variable Name (case insensitive)	Type	Max. Length	Allowed Values	Description
loginName	string	64 chars		Account Username (case sensitive)
loginPassword	string	128 chars		Account Password (case sensitive)
<i>accountID</i>	integer			If specified, this is the Account ID of a Tier 2 Reseller account, and “loginName” and “loginPassword” must be the login credentials of the Tier 1 Reseller.
orderNumber	integer			This is the order number for the PAC order
<i>templateID</i>	integer			If specified, this overrides Sectigo's default choice of validation email template to be used to validate this certificate. Talk to your account manager if you would like to set up one or more of your own validation email templates that can be referenced by this parameter

2. Response

Line	Possible Value(s)
<i>Mime-Type</i>	text/plain
Line 1: <i>StatusCode</i>	0 = Successful -1 = Request was not made over https! -2 = Unrecognised argument! -3 = The ‘xxxx’ argument is missing! -4 = The value of the ‘xxxx’ argument is invalid! -14 = An unknown error occurred! -16 = Permission denied! -17 = Request used GET rather than POST!

2.2.1 If *StatusCode* < 0

Line	Possible Value(s)
Line 2: <i>Error Message</i>	<i>Textual representation of error message. See Status Code Possible Value(s)</i>